



Oil Pattern Distance **Forward Oil Total Tank Configuration** 

43 16.75 mL N/A

**Reverse Brush Drop Reverse Oil Total Tank A Conditioner** 

36 10.1 mL Kegel Oil Per Board **Volume Oil Total Tank B Conditioner** 

50 ul 26.85 mL Kegel

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	4	18	Α	148	0.0	7.6	7.6	7400
2	8L	8R	4	18	В	100	7.6	17.8	10.2	5000
3	11L	11R	3	22	Α	57	17.8	27.1	9.3	2850
4	13L	13R	2	10	В	30	27.1	29.9	2.8	1500
5	2L	2R	0	26	Α	0	29.9	43.0	13.1	0

2 14L 14R 2 22 B 26 33.0 26.8 -6.2 1300 3 12L 12R 2 22 A 34 26.8 20.6 -6.2 1700 4 10L 10R 2 18 B 42 20.6 15.5 -5.1 2100 5 9L 9R 2 18 A 46 15.5 10.4 -5.1 2300 6 7L 7R 2 14 B 54 10.4 6.5 -3.9 2700		START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
3 12L 12R 2 22 A 34 26.8 20.6 -6.2 1700 4 10L 10R 2 18 B 42 20.6 15.5 -5.1 2100 5 9L 9R 2 18 A 46 15.5 10.4 -5.1 2300 6 7L 7R 2 14 B 54 10.4 6.5 -3.9 2700	1	2L	2R	0	30	Α	0	43.0	33.0	-10.0	0
4 10L 10R 2 18 B 42 20.6 15.5 -5.1 2100 5 9L 9R 2 18 A 46 15.5 10.4 -5.1 2300 6 7L 7R 2 14 B 54 10.4 6.5 -3.9 2700	2	14L	14R	2	22	В	26	33.0	26.8	-6.2	1300
5 9L 9R 2 18 A 46 15.5 10.4 -5.1 2300 6 7L 7R 2 14 B 54 10.4 6.5 -3.9 2700	3	12L	12R	2	22	Α	34	26.8	20.6	-6.2	1700
6 7L 7R 2 14 B 54 10.4 6.5 -3.9 2700	4	10L	10R	2	18	В	42	20.6	15.5	-5.1	2100
	5	9L	9R	2	18	Α	46	15.5	10.4	-5.1	2300
7 2L 2R 0 14 A 0 6.5 0.0 -6.5 0	6	7L	7R	2	14	В	54	10.4	6.5	-3.9	2700
	7	2L	2R	0	14	Α	0	6.5	0.0	-6.5	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5,23	1.6	1.02	1.02	1.6	5.23



